

Application

Compact floodlight with 1/2" I.P.S. nipple for use with a variety of mounting accessories. Designed to illuminate architectural features, signage, landscaping, or to provide general illumination in a space. Pair with a variety of optical accessories.

Materials

Clear safety glass  
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners  
316 stainless steel 1/2" IPS threaded nipple  
Pure anodized aluminum reflector  
Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 2.0 lbs.

EPA (Effective projection area): 0.1 sq. ft.

Electrical

Operating voltage	24VDC (remote power supply req.)
Minimum start temperature	-40° C
LED module wattage	7.9W
System wattage	9.0W
Controllability	Non-Dimming
Color rendering index	Ra > 80
Luminaire lumens	878lm
LED service life (L70)	60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:

BEGA Product:

Project:

Modified:


Available options

AMB	Amber LED
B70050	Elliptical spread lens
B70755	Glare shield · 180°
CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL finish

Available accessories

B19591	Remote driver box · Static white
B19593	Surface mount conduit wiring box
B19594	Direct burial wiring box
B70204	Earth spike
B70249	Pole cap · 3" O.D. pole tenon
B70252	Wood screw
B70280	Tube clamp
B70283	Screw clamp
B70379	Pole mount arm · 1/2" I.P.S. nipple floodlights
B71042	Pole coupler
B79511	Mounting block

See individual accessory spec sheet for details.



Compact floodlight · Wide beam · 24V DC

	LED	□	A	B	C
B77699	7.9W	47°	4 1/8	6	4 3/8

