# Application

Compact floodlight with mounting canopy for direct mounting to horizontal or vertical surfaces. Designed to illuminate architectural features, signage, landscaping, or to provide general illumination in a space. Pair with a variety of optical accessories.

#### Materials

Clear safety glass

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy High temperature silicone gasket

Mechanically captive stainless steel fasteners

Pure anodized aluminum reflector

Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 65

Weight: 5.1 lbs.

EPA (Effective projection area): 0.3 sq. ft.

#### Electrical

Operating voltage 120-277V AC
Minimum start temperature -30° C
LED module wattage 19.2 W
System wattage 22.0 W

Controllability 0-10V, TRIAC, and ELV dimmable

Color rendering index Ra > 90 Luminaire lumens 1851 lm LED service life (L70) 60000 hrs

## LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

#### Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

# Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
Natural Bronze (NTB) RAL:

CUS:

# Type:

**BEGA Product:** 

Project: Modified:

#### Available options


B70060 Elliptical spread lens
B70720 Glare shield · 360°
B70757 Glare shield · 180°
B70796 Concentric ring louver
CUS Custom finish

DALI Digital addressable lighting interface

FSC Fusing

MGU Marine grade undercoat NTB Natural bronze (premium finish)

RAL RAL finish



### Compact floodlight · Narrow beam

	LED		Α	В	С	D	
B77701	19.2 W	26°	61/4	87/8	61/2	37/8	

