

Application

The unshielded light of this luminaire is ideally suited for structuring and dividing open spaces. The construction is robust enough for people to sit or stand on. BEGA light design elements are like luminous sculptures, ideal for sophisticated arrangements of open spaces, along pathways and on roof terraces.

Materials

White UV-stabilized acrylic diffuser
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
Mechanically captive stainless steel fasteners
Galvanized steel anchorage

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 43.4 lbs.

Electrical

Operating voltage 120-277VAC
Minimum start temperature -30° C
LED module wattage 16.8 W
System wattage 21.0 W
Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 859 lm
LED service life (L70) 60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:

Type:

BEGA Product:

Project:


Modified:

Available options

CUS Custom finish
FSC Fusing
MGU Marine grade undercoat
RAL RAL finish

Included (available for pre-shipment)

B79812 Anchorage kit



Urban furniture · Unshielded bollard			
	LED	A	B
B77764	16.8 W	15 3/4	18

