


Tools Required:

3mm hex key
4mm hex key
5mm hex key
Adjustable wrench

Protection Class: IP65

Weight: 22.0 lbs.


Dimensions

A: 19-3/4"
B: 40-5/8 "
C: 32-5/8 "


Notice to Installer for 77 910:

1. For pole top applications only.
2. Slip fits 3" O.D. poles only.
3. LED module and integral driver provided by BEGA.
4. Pole top luminaire supplied with 25 feet of cable to route through pole.

77 910 - installation:

1. Route the luminaire wiring through to the pole base and slip luminaire over the top of the pole.
2. Secure luminaire by tightening set screws on pole fitter, evenly.
3. Insert shade reflector into luminaire housing such that the drainage hole on the reflector rim is turned to the pole side. Tighten four (4) hex screws evenly and securely.
4. Undo cap nut in luminaire housing and install optical unit according to directional label, "FRONT". Tighten nuts to secure.
5. Install lens after and tighten screw to secure. Make sure the gasket is seated properly.
6. Make supply wiring connections to luminaire wires in pole base:
MAIN VOLTAGE SUPPLY WIRE TO BLACK LUMINAIRE WIRE
NEUTRAL (COMMON) SUPPLY WIRE TO WHITE LUMINAIRE WIRE
GREEN GROUND WIRE TO GREEN LUMINAIRE WIRE

Relamping/Maintenance

NO relamping necessary.

Accessories

Please refer to the appropriate accessory installation sheet for further instruction when applicable.

Replacement Parts

Description	Part No
Acrylic lens cylinder	150366
Lens gasket	830439
LED driver	75983-02
LED module (3000K)	LED-0276/830
LED module (4000K)	LED-0276/840

Lamp: 15.8W LED

Product Safety Warnings:

CAUTION - RISK OF FIRE. THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED. SUITABLE FOR WET LOCATIONS.

MIN 90°C SUPPLY CONDUCTORS.

ATTENTION - RISQUE D'INCENDIE, CE PRODUIT DOIT ÊTRE INSTALLÉ SELON LE CODE D'INSTALLATION PERTINENT, PAR UNE PERSONNE QUI CONNAÎT BIEN LE PRODUIT ET SON FONCTIONNEMENT AINSI QUE LES RISQUES INHÉRENTS. CONVIENT AUX EMPLACEMENTS MOUILLÉS.

LES FILS D'ALIMENTATION 90°C MIN.
