


Tools Required:

- 4mm hex head screwdriver

Overview:

LED Watts: 23.6W  
System Watts: 28.0W  
Controllability: 0-10V dimmable  
Weight: 27.6 lbs.  
Protection Class: IP65



Dimensions

A: 26-5/8  
B: 46-1/4  
C: 40-1/8



Notice to Installer:

1. For pole top applications only.
2. Slip fits 3" OD poles or tenons only. Requires a minimum 4" length of straight dia. pole/tenon for proper installation.
3. Pole top luminaire is provided with a 25' wire bundle to route through the pole for supply wiring connections.

Installation: Luminaire

1. Route the luminaire wiring through the pole to the base and slip fit the luminaire over the top of the pole.
2. Aim luminaire in desired direction. Secure luminaire into place by tightening the (6) 4mm set screws on the pole fitter evenly. Set screws must be tightened to 12Nm.
3. Make supply wiring connections in base of pole:  
MAIN VOLTAGE SUPPLY WIRE TO BLACK LUMINAIRE WIRE  
NEUTRAL (COMMON) SUPPLY WIRE TO WHITE LUMINAIRE WIRE  
GREEN GROUND WIRE TO GREEN LUMINAIRE WIRE  
0-10V Dimming (if applicable):  
DIMMING CONTROL (+) TO POSITIVE LUMINAIRE DIM CONTROL WIRE  
DIMMING CONTROL (-) TO NEGATIVE LUMINAIRE DIM CONTROL WIRE

Accessories

Please refer to the appropriate accessory installation sheet for further instruction when applicable.

Maintenance:

Clean regularly with solvent-free cleaner removing dirt and debris. Do not use high pressure cleaners.

Replacement Parts

See label inside of fixture for LED replacement part number.  
Consult factory for all other replacement components.

## Product Safety Warnings:

**THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED.  
SUITABLE FOR WET LOCATIONS.  
MIN 60°C SUPPLY CONDUCTORS.**

**CE PRODUIT DOIT ÊTRE INSTALLÉ SELON LE CODE D'INSTALLATION PERTINENT, PAR UNE PERSONNE QUI CONNAÎT BIEN LE PRODUIT ET SON FONCTIONNEMENT AINSI QUE LES RISQUES INHERENTS.  
CONVIENT AUX EMPLACEMENTS MOUILLÉS.  
LES FILS D'ALIMENTATION 60°C MIN.**