

Application

Pole-top luminaire with asymmetric wide beam light distribution. These luminaires are designed to illuminate roadways, squares, driveways and pedestrian areas.

Materials

Optically textured UV-stabilized acrylic diffuser
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
Mechanically captive stainless steel fasteners
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 27.6lbs.

EPA (Effective projection area): 2.4 sq. ft.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	23.6W
System wattage	28.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	3558lm
LED service life (L70)	60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

CUS	Custom finish
DALI-2	Digital addressable lighting interface
FSC	Fusing
MGU	Marine grade undercoat
RAL	RAL finish



Pole-top luminaire · Asymmetric wide beam			
	LED	A	B
B77911	23.6W	26 ⁵ / ₈	46 ¹ / ₄