

Application

Linear in-grade floodlight with asymmetric light distribution. Designed to illuminate architectural features, signage and building facades. These luminaires are designed to bear pressure loads up to 2200 lbs. from vehicles with pneumatic tires. The luminaires must not be used for traffic lanes where they are subject to horizontal pressure from vehicles braking, accelerating and changing direction.

Materials

- Corrosion-resistant 304 grade stainless steel
- High temperature silicone gasket
- Aluminum installation housing
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 67

Weight: 29.8 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage18.8 W
- System wattage23.0 W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens2699 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:
BEGA Product:
Project:
Modified:

Included (available for pre-shipment)
BB7916LED Installation housing



In-grade luminaire · Asymmetric				
	LED	A	B	C
B77918	18.8 W	3 1/2	39 3/8	5

