


BEGA

Photometric Filename: 77950.IES

TEST: NA
TEST LAB: BEGA
DATE: 02/25/2014
LUMINAIRE: 77 950
LAMP: 50.6W LED




Characteristics

IES Classification	Type III
Longitudinal Classification	Short
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	4530
Downward Total Efficiency	N.A.
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	79
Total Luminaire Watts	57
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Max. Cd.	2705.6 (285H, 65V)
Max. Cd. (<90 Vert.)	2705.6 (285H, 65V)
Max. Cd. (At 90 Deg. Vert.)	0 (0.0%Lum)
Max. Cd. (80 to <90 Deg. Vert.)	1000.5 (22.1%Lum)
Cutoff Classification (deprecated)	N.A. (absolute)


Lum. Classification System (LCS)

LCS Zone	Lumens	%Lamp	%Lum
FL (0-30)	540.3	N.A.	11.9
FM (30-60)	1766.4	N.A.	39.0
FH (60-80)	1035.8	N.A.	22.9
FVH(80-90)	74.5	N.A.	1.6
BL (0-30)	317.7	N.A.	7.0
BM (30-60)	501.4	N.A.	11.1
BH (60-80)	280.6	N.A.	6.2
BVH(80-90)	13.0	N.A.	0.3
UL (90-100)	0.0	N.A.	0.0
UH (100-180)	0.0	N.A.	0.0
Total	4529.7	N.A.	100.0

BUG Rating B1-U0-G1



Mounting Height = 15 ft. Grid Spacing = 14 ft.



In the interest of product improvement, BEGA reserves the right to make technical changes without notice.