

Application

BEGA system bollard luminaire tube without components. BEGA system bollard tubes are designed for easy attachment to system bollard heads using an interlocking mechanism. An accompanying bollard head must be selected for proper installation. Mounting system allows for luminaire to be adjusted independent of anchor bolt orientation.

Materials

- Die-cast aluminum
- Extruded aluminum
- Mechanically captive stainless steel fasteners
- Galvanized steel anchorage

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 13.7 lbs.

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- | | |
|----------------------|--------------|
| Black (BLK) | Bronze (BRZ) |
| Silver (SLV) | White (WHT) |
| Natural Bronze (NTB) | RAL: |
| CUS: | |

Type:
BEGA Product:
Project:
Modified:

Available options

- | | |
|-------|--|
| 70896 | Direct burial anchorage (replaces included anchorage kit, pre-shippable) |
| CUS | Custom finish |
| MGU | Marine grade undercoat |
| NTB | Natural bronze (premium finish) |
| RAL | RAL finish |

Included (available for pre-shipment)

- | | |
|--------|---------------|
| B79818 | Anchorage kit |
|--------|---------------|




	A	B
B84001	8 ⁵ / ₈	14 ³ / ₄



System bollard summary · Square

The overview provides a compact summary of the possibilities for combining the various bollard heads with the bollard tubes and their additional functions.

For each bollard head you can find matching bollard tubes with and without components.

System bollard heads with compatible tubes							
BEGA bollard tubes □ in inches		□ 6 1/2	□ 8 5/8	□ 6 1/2	□ 8 5/8	□ 6 1/2	□ 8 5/8
	Without components in two heights	•	•	•	•	•	•
	With integral PIR motion sensor	•	•	•	•	•	•
	With drive-through protection		•		•		•
	With integral GFCI outlet		•		•		•
	Wood bollard tubes	•	•	•	•	•	•

Compatible heads · □ 8 5/8

System bollard head · Unshielded with safety guard · 360°

	LED	A	B
B84681	15.7 W	8 5/8	9 1/4

System bollard head · Shielded · 360°

	LED	A	B
B84691	25.2 W	8 5/8	7 1/2

System bollard head · Non-illuminated cap

	A	B
B71125	8 5/8	0 3/4