

Application

Bollards with rotationally symmetric light distribution designed to provide glare-free illumination perfect for squares, pathways and entrances. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

- Clear safety glass
- Die-cast aluminum
- Extruded aluminum
- Mechanically captive stainless steel fasteners
- Silicone applied robotically to casting, plasma treated for increased adhesion
- High temperature silicone gasket
- Galvanized steel anchorage
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-30° C
- LED module wattage25.9W
- System wattage34.0W
- Controllability0-10V dimming down to 1%
- Color rendering indexRa > 80
- Luminaire lumens1700lm
- LED service life (L70)60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- Natural Bronze (NTB)
- CUS:
- Bronze (BRZ)
- White (WHT)
- RAL:

Type:

BEGA Product:

Project:

Modified:

Available options

- 70896Direct burial anchorage (replaces included anchorage kit, pre-shippable)
- CUSCustom finish
- FSCFusing
- MGUMarine grade undercoat
- NTBNatural bronze (premium finish)
- RALRAL finish

Included (available for pre-shipment)

- B79818Anchorage kit



Bollard · Shielded

	LED	A	B
B84062	25.9W	8 ³ / ₄	47 ³ / ₈

