

Cable (6 ft.)

Replacement Parts:

LED-0488/930 LED Module LED Driver 75946 Glass Lens 140850

86067

С

Dimensions

A: 4-1/8" 15-3/8 C: 4-3/8 "



Protection Class: IP65

Weight: 2.6 lbs.

Luminaire 84 067:

Housing: Two-piece die-cast aluminum housing. Reflector made of pure annodized aluminum. Clear safety glass.

Electrical: 3W LED luminiare, 4 total system watts, -30°C start temperature. Integral 12V AC driver provided. Standard LED color temperature is 3000K with an >90 CRI.

IMPORTANT: For use with magnetic landscape transformers ONLY.

Warranty: 3 year manufacturer warranty.

Notice to Installer for 84 067:

WARNING: LEDs are high quality electrical components. Please avoid opening upper electrical compartment and do NOT touch LED module.

WARNING: RISK OF ELECTRIC SHOCK.

ATTENTION - RISQUE DE CHOC.

Install all luminaires 10 feet or more from pool, spa or fountain.

- 1. Compatible for use with 12-24V AC input voltage.
- 2. Voltage must NOT drop below 10V.
- 3. Turn main power OFF before start of installation.
- 4. Vertical rotation: +80°/-50°
- 5. No tools necessary for rotation adjustment.
- 6. Wiring connections must be water tight.

84 067 installation:

- 1. Establish planned fixture location and provide supply wiring.
- 2. Make wiring connections. For maximum wire run lengths, see table below.
- 3. Push luminaire with earth spike vertically into the soil until stability is achieved.
- 4. If necessary compact soil around the earth spike.
- 5. Adjust position of the floodlight and tighten thumbscrew.

_					
Max. Run Length (ft) Per Wire Size: 2 Volt drop					
Connected	Wire Size (AWG)				
LED Watts	18	16	14	12	10
40	46	73	116	185	294
30	61	97	155	246	392
20	92	146	232	369	588
15	122	195	309	492	784
10	183	292	464	738	1176
5	366	585	928	1477	2353

Integral 3W LED Module Lamp:

(No replacement necessary)