

Application

Floodlight with earth spike and adjustable knuckle. This luminaire is ideally suited for highlighting architecture and landscape elements around the home and garden. The earth spike mounting allows for flexible installation as design parameters change over time. Low voltage magnetic transformer required for operation.

Materials

Clear safety glass  
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
High temperature silicone gasket  
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 2.6 lbs.

Electrical

Operating voltage	12VAC
Minimum start temperature	-40° C
LED module wattage	3.0W
System wattage	4.0W
Controllability	Non-Dimming
Color rendering index	Ra > 90
Luminaire lumens	332lm
LED service life (L70)	60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details


Finish

BEGA Black polyester powder coat finish. Custom colors not available.

Type:  
BEGA Product:  
Project:  
Modified:

Available accessories  
B536 Low voltage magnetic transformer · 300W  
See individual accessory spec sheet for details.



Garden floodlight with earth spike · Symmetric · 12V AC					
	LED		A	B	C
B84067	3.0W	32°	4 <sup>1</sup> / <sub>8</sub>	15 <sup>3</sup> / <sub>8</sub>	4 <sup>3</sup> / <sub>8</sub>