

Application

Surface washer floodlights with 1/2" I.P.S. nipple for use with a variety of mounting accessories. Ideal for the direct or indirect floodlighting of walls, signage or ceilings.

Materials

Clear safety glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Silicone applied robotically to casting, plasma treated for increased adhesion
316 stainless steel 1/2" IPS threaded nipple
Pure anodized aluminum reflector surface

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 6.2 lbs.

EPA (Effective projection area): 0.8 sq. ft.

Electrical

Operating voltage 120-277VAC
Minimum start temperature -30° C
LED module wattage 19.4 W
System wattage 24.0 W
Controllability 0-10V, TRIAC, and ELV dimmable
Color rendering index Ra > 90
Luminaire lumens 2668 lm
LED service life (L70) 60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
Natural Bronze (NTB) RAL:
CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

CUS Custom finish
MGU Marine grade undercoat
NTB Natural bronze (premium finish)
RAL RAL Classic, matte finish



Surface washer floodlight · Asymmetric

	LED	β	A	B	C
B84099	19.4 W	72°	10 1/4	4 1/8	13 1/8

