

Application

A pole-top luminaire with symmetric, Type V distribution. Ideal for illuminating plazas and other pedestrian spaces while adding visual interest.

Materials

- Clear UV-stabilized acrylic diffuser
- A380 aluminum alloy
- 316 grade stainless steel
- High temperature silicone gasket
- Integral surge protector
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 22.0 lbs.

EPA (Effective projection area): 1.93 sq. ft.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-20° C
- LED module wattage47.7 W
- System wattage54.0 W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens6457 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Type:


BEGA Product:

Project:

Modified:

Available options

- CUSCustom finish
- FSCFusing
- MGUMarine grade undercoat
- RALRAL finish



Pole-top luminaire · Symmetric			
	LED	A	B
B84101	47.7 W	8 ⁵ / ₈	34 ¹ / ₂

