

Application
Building elements with adjustable luminaire head for maximum flexibility. Light building elements are luminous design features for public areas. They are ideally suited for delineating and structuring interior and exterior spaces such as landscape areas, plazas, building entrances and atria.

Materials
Clear safety glass
Extruded aluminum pole shaft
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
Silicone applied robotically to casting, plasma treated for increased adhesion
Covered handhole with hardware and grounding provisions provided
Mechanically captive stainless steel fasteners
Zinc plated carbon steel anchor bolts with template
2-piece aluminum cover provided with anchor base
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 35.1 lbs.


Electrical
Operating voltage 120-277V AC
Minimum start temperature -30° C
LED module wattage 19.4 W
System wattage 24.0 W
Controllability 0-10V, TRIAC, and ELV dimmable
Color rendering index Ra > 90
Luminaire lumens 2661 lm
LED service life (L70) 60000 hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors
Black (BLK) White (WHT)
Bronze (BRZ) Silver (SLV)
RAL: CUS:



Building element · Asymmetric · Single				
	LED	A	B	C
B84103	19.4 W	10 1/4	102 7/8	14

Type:
BEGA Product:
Project:
Modified:

Available options
CUS Custom finish
FSC Fusing
MGU Marine grade undercoat
RAL RAL finish

Included (available for pre-shipment)
B79818 Anchorage kit

