

Application

With an elegant form and extraordinary glare control, this pole top luminaire provides visual interest both day and night. Designed to illuminate parking areas, roadways and walkways. Provided with slip fitter to fit 3" O.D. poles.

Materials

- Optically textured UV-stabilized acrylic diffuser
- Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Integral surge protector
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 21.4 lbs.

EPA (Effective projection area): 0.7 sq. ft.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-30° C
- LED module wattage23.6W
- System wattage28.0W
- Controllability0-10V dimming down to 1%
- Color rendering indexRa > 80
- Luminaire lumens2297 lm
- LED service life (L70)60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)

Silver (SLV)

RAL:
- Bronze (BRZ)

White (WHT)

CUS:

Type:
BEGA Product:
Project:
Modified:

- Available options
- CUS

DALI

FSC

MGU

RAL

SRG
- Custom finish


Digital addressable lighting interface

Fusing

Marine grade undercoat

RAL finish

Surge protection



Edge-lit pole-top luminaire · Asymmetric			
	LED	A	B
B84121	23.6W	20 ^{5⁄₈}	22 ^{1⁄₄}

