

Application

Designed for public spaces to provide illumination and internet from a single source, the WiFi hardware of your choice may be easily integrated into this BEGA luminaire. With a convenient mounting bracket for a router concealed behind an access door, and four integral dual-band antennas enclosed by a composite section of housing, the form of this luminaire is sleek yet practical. DarkSky Approved (2700K and 3000K only).

Materials

Clear UV-stabilized acrylic diffuser  
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
Extruded aluminum  
High temperature silicone gasket  
Covered handhole with hardware and grounding provisions provided  
Mechanically captive stainless steel fasteners  
Integral surge protector  
Anchorage must be buried  
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 132.0lbs.

EPA (Effective projection area): 11.8 sq. ft.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	47.7 W
System wattage	52.0W
Controllability	0-10V dimming down to 1%
Color rendering index	Ra > 80
Luminaire lumens	5749lm
LED service life (L70)	60000hrs

LED color temperature

4000K (K4)  
3500K (K35)  
3000K (K3) (DarkSky Approved)  
2700K (K27) (DarkSky Approved)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:

BEGA Product:

Project:

Modified:

Available options

CUS	Custom finish
MGU	Marine grade undercoat
RAL	RAL finish



Building element · Symmetric					
	LED	A	B	C	D
B84122	47.7 W	8 <sup>5</sup> / <sub>8</sub>	27 <sup>1</sup> / <sub>2</sub>	196 <sup>7</sup> / <sub>8</sub>	39 <sup>3</sup> / <sub>8</sub>

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805)684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com  
© copyright BEGA 2025 Updated 07/11/25