


BEGA

Photometric Filename: 84126.ies

TEST: N/A
TEST LAB: BEGA
DATE: 2/28/17
LUMINAIRE: 84 126
LAMP: 39.2W LED




Characteristics

IES Classification	Type II
Longitudinal Classification	Very Short
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	4781
Downward Total Efficiency	N.A.
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	110
Total Luminaire Watts	43.5
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Max. Cd.	1829.2 (275H, 32.5V)
Max. Cd. (<90 Vert.)	1829.2 (275H, 32.5V)
Max. Cd. (At 90 Deg. Vert.)	0 (0.0%Lum)
Max. Cd. (80 to <90 Deg. Vert.)	203.8 (4.3%Lum)
Cutoff Classification (deprecated)	N.A. (absolute)


Lum. Classification System (LCS)

LCS Zone	Lumens	%Lamp	%Lum
FL (0-30)	486.8	N.A.	10.2
FM (30-60)	1418.3	N.A.	29.7
FH (60-80)	533.6	N.A.	11.2
FVH(80-90)	32.0	N.A.	0.7
BL (0-30)	479.4	N.A.	10.0
BM (30-60)	1360.3	N.A.	28.5
BH (60-80)	453.4	N.A.	9.5
BVH(80-90)	17.2	N.A.	0.4
UL (90-100)	0.0	N.A.	0.0
UH (100-180)	0.0	N.A.	0.0
Total	4781.0	N.A.	100.0

BUG Rating B2-U0-G1



Mounting Height = 15 ft. Grid Spacing = 12 ft.



In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2017

9/11/2017