

Application

With an elegant form and extraordinary glare control, this pole top luminaire provides visual interest both day and night. Designed to illuminate large parking areas and plazas. Provided with slip fitter to fit 3" O.D. poles.

Materials

Optically textured UV-stabilized acrylic diffuser
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Mechanically captive stainless steel fasteners
Integral surge protector
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 61.7 lbs.

EPA (Effective projection area): 1.6 sq. ft.

Electrical

Operating voltage 120-277VAC
Minimum start temperature -30° C
LED module wattage 46.4 W
System wattage 52.0 W
Controllability 0-10V dimming down to 1%
Color rendering index Ra > 80
Luminaire lumens 4734 lm
LED service life (L70) 60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

CUS Custom finish
DALI Digital addressable lighting interface
FSC Fusing
MGU Marine grade undercoat
RAL RAL finish



Edge-lit pole-top luminaire · Symmetric

	LED	A	B
B84147	46.4 W	29 1/2	32 3/8

