

Application

With an elegant form and extraordinary glare control, this pole top luminaire provides visual interest both day and night. Designed to illuminate large parking areas, roadways and walkways. Provided with slip fitter to fit 3" O.D. poles.

Materials

- Optically textured UV-stabilized acrylic diffuser
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Integral surge protector
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 61.7 lbs.

EPA (Effective projection area): 1.6 sq. ft.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage47.2 W
- System wattage52.0 W
- Controllability0-10V dimming down to 1%
- Color rendering indexRa > 80
- Luminaire lumens4557 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- |              |              |
|--------------|--------------|
| Black (BLK)  | Bronze (BRZ) |
| Silver (SLV) | White (WHT)  |
| RAL:         | CUS:         |

Type:


BEGA Product:

Project:

Modified:

Available options

- |      |                                        |
|------|----------------------------------------|
| CUS  | Custom finish                          |
| DALI | Digital addressable lighting interface |
| FSC  | Fusing                                 |
| MGU  | Marine grade undercoat                 |
| RAL  | RAL finish                             |
| SRG  | Surge protection                       |



Edge-lit pole-top luminaire · Asymmetric

|        | LED    | A      | B      |
|--------|--------|--------|--------|
| B84148 | 47.2 W | 29 1/2 | 32 3/8 |

