

Application
The design of this in-grade floodlight makes it possible to fully illuminate a vertical surface, from the ground up to the edge of the roof. The lower limit of the light distribution is straight without the usual scallop.

Materials
Hand-blown crystal glass
Corrosion-resistant 304 grade stainless steel
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Mechanically captive stainless steel fasteners
Silicone optic with excellent high temperature and UV stability
Pure anodized aluminum reflector
NRTL listed to North American Standards, suitable for wet locations
Protection class IP 67

Weight: 18.7 lbs.

Electrical
Operating voltage 120V or 277V AC
Minimum start temperature -30° C
LED module wattage 24.6W
System wattage 29.2W
Controllability 0-10V, TRIAC, and ELV dimmable
Color rendering index Ra > 80
Luminaire lumens 2330 lm
LED service life (L70) 60000hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
Natural cast bronze. Time and weather factors will create the natural patina of bronze.

Type:
BEGA Product:
Project:
Modified:

Available options
NTB Natural bronze (premium finish)

Included (available for pre-shipment)
BB84618 Installation housing



In-grade floodlight · Wall washer · Bronze						
	LED	□	A	B	C	D
B84175	24.6W	20°x91°	11 1/4	13 5/8	4 1/4	2 3/8

