Application

Compact performance floodlight with 1/2" I.P.S. nipple for use with a variety of mounting accessories. Designed to illuminate architectural features, landscaping, signage, and for general illumination of a space. Pair with a variety of optical accessories.

Materials

Clear safety glass

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy Silicone applied robotically to casting, plasma treated for increased adhesion

High temperature silicone gasket

316 stainless steel 1/2" IPS threaded nipple

Pure anodized aluminum reflector surface

Silicone optic with excellent high temperature and UV stability

BEGA Hybrid Optics®

 $\ensuremath{\mathsf{NRTL}}$ listed to North American Standards, suitable for wet locations Protection class IP 65

Weight: 4.0 lbs.

EPA (Effective projection area): 0.22 sq. ft.

Electrical

Operating voltage 120-277V AC
Minimum start temperature -30° C
LED module wattage 16.8 W
System wattage 20.0 W

Controllability 0-10V, TRIAC, and ELV dimmable

Color rendering index Ra > 90 Luminaire lumens 1949 lm LED service life (L70) 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
Natural Bronze (NTB) RAL:
CUS:



Performance floodlight · Narrow beam

	LED	β	Α	В	С
B84216	16.8W	19°	53/4	83/4	37/8

Type:

BEGA Product:

Project: Modified:

Available options

B71119 Concentric ring louver

B71120 Elliptical spread lens (Not compatible with

internal louver)
CUS Custom finish
FSC Fusing

MGU Marine grade undercoat NTB Natural bronze (premium finish) RAL RAL Classic, matte finish

Available accessories

R19593

D19090	Surface mount conduit wining box
B19594	Direct burial wiring box
B70204	Earth spike
B70249	Pole cap · 3" O.D. pole tenon
B70252	Wood screw
B70280	Tube clamp
B70283	Screw clamp
B70379	Pole mount arm · 1/2" I.P.S. nipple floodlights
B71042	Pole coupler
B71118	Glare shield · 180°
B79511	Mounting block
B79829	Glare shield · 360°

Surface mount conduit wiring box

See individual accessory spec sheet for details.

