

**Application**  
The fully shielded design of this bollard provides visual comfort while illuminating ground surfaces. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation. DarkSky Approved (2700K and 3000K only).

**Materials**  
Clear safety glass  
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
Zinc plated carbon steel anchor bolts with template  
Pure anodized aluminum reflector

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 65

**Weight:** 12.8lbs.

**Electrical**  
Operating voltage 120-277V AC  
Minimum start temperature -30° C  
LED module wattage 11.5 W  
System wattage 15.0W  
Controllability 0-10V, TRIAC, and ELV dimmable  
Color rendering index Ra > 80  
Luminaire lumens 1475 lm  
LED service life (L70) 60000 hrs

**LED color temperature**  
4000K (K4)  
3500K (K35)  
3000K (K3) (DarkSky Approved)  
2700K (K27) (DarkSky Approved)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**  
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

**Available colors**  
Black (BLK) Bronze (BRZ)  
Silver (SLV) White (WHT)  
Natural Bronze (NTB) RAL:  
CUS:

Type:  
BEGA Product:  
Project:  
Modified:

**Available options**  
70895 Direct burial anchorage (replaces included anchorage kit, pre-shippable)  
CUS Custom finish  
MGU Marine grade undercoat  
NTB Natural bronze (premium finish)  
RAL RAL finish

**Included (available for pre-shipment)**  
B79817 Anchorage kit



Shielded bollard · Asymmetric wide beam			
	LED	A	B
B84220	11.5W	6 1/4	37 1/4

