

Application

Light building elements are luminous design features for public areas. They are ideally suited for delineating and structuring interior and exterior spaces such as landscape areas, plazas, building entrances, and atria. An internal mechanism allows the optical system to be adjusted in steps from 0°, 15° and 30° on either side of the luminaire.

Materials

- Clear safety glass
- Extruded aluminum
- Die-cast aluminum
- Mechanically captive stainless steel fasteners
- High temperature silicone gasket
- Integral surge protector
- Galvanized steel anchorage
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 88.6lbs.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-40° C
- LED module wattage29.0W
- System wattage34.0W
- Controllability0-10V dimmable
- Color rendering indexRa > 90
- Luminaire lumens2324 lm
- LED service life (L70)60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- RAL:
- Bronze (BRZ)
- White (WHT)
- CUS:



Building element · Adjustable

	LED	A	B	C
B84221	29.0W	10 ⁵ / ₈	73 ¹ / ₈	137 ³ / ₄

Type:

BEGA Product:

Project:

Modified:

Available options

- B71140 Direct burial anchorage (replaces included anchorage kit, pre-shippable)

Included (available for pre-shipment)

- B79802 Buried anchorage kit

