

Application

Compact performance floodlight with mounting canopy for mounting to horizontal or vertical surfaces. Designed to illuminate architectural features, landscaping, signage, and for general illumination of a space. Pair with a variety of optical accessories.

Materials

Clear safety glass  
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
Mechanically captive stainless steel fasteners  
High temperature silicone gasket  
Pure anodized aluminum reflector surface  
Silicone optic with excellent high temperature and UV stability  
BEGA Hybrid Optics®

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 10.1 lbs.

EPA (Effective projection area): 0.43 sq. ft.

Electrical

Operating voltage 120-277VAC  
Minimum start temperature -40° C  
LED module wattage 60.3W  
System wattage 69.0W  
Controllability 0-10V dimmable  
Color rendering index Ra > 90  
Luminaire lumens 6952lm  
LED service life (L70) 60000hrs

LED color temperature

4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)  
Silver (SLV) White (WHT)  
Natural Bronze (NTB) RAL:  
CUS:



Performance floodlights · Wide beam

	LED	□	A	B	C	D
B84224	60.3W	54°	8 1/4	12 3/8	5 1/4	5 1/8

Type:

BEGA Product:

Project:

Modified:

Available options

B71123 Elliptical Spread Lens (Not compatible with internal louver)  
CUS Custom finish  
FSC Fusing  
MGU Marine grade undercoat  
NTB Natural bronze (premium finish)  
RAL RAL finish

Available accessories

B71121 Glare shield · 180°  
B79831 Glare shield · 360°

See individual accessory spec sheet for details.

