## Application

Light building element with asymmetric light distribution. Light building elements are luminous design features for public areas. They are usually suited for delineating and structuring interior and exterior spaces such as landscape areas, plazas, building entrances and atria.

#### Materials

Clear safety glass with printed optical texture

Extruded aluminum pole shaft

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy

High temperature silicone gasket

Mechanically captive stainless steel fasteners

Integral surge protector

Galvanized steel anchorage

Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 65

Electrical

Operating voltage 120-277V AC
Minimum start temperature
LED module wattage 17.6 W
System wattage 22.0 W

Controllability 0-10V dimmable

Color rendering index Ra > 90 Luminaire lumens 2521 lm LED service life (L70) 60000 hrs

## LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

#### Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

## Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:



Building element · Asymmetric · Single					
	LED	А	В	С	
B84240	17.6W	91/2	12³/ <sub>8</sub>	1771/8	

Type:

**BEGA Product:** 

Project: Modified:

# Available options

B71140 Direct burial anchorage (replaces included

anchorage kit, pre-shippable)

CUS Custom finish

FSC Fusing

MGU Marine grade undercoat RAL Classic, matte finish

### Included (available for pre-shipment)

B79802 Buried anchorage kit

