

Application

Light building element with asymmetric light distribution. Light building elements are luminous design features for public areas. They are usually suited for delineating and structuring interior and exterior spaces such as landscape areas, plazas, building entrances and atria.

Materials

- Clear safety glass with optical texture
- Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
- Extruded aluminum pole shaft
- High temperature silicone gasket
- Integral surge protector
- Galvanized steel anchorage
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 132.1 lbs.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-20° C
- LED module wattage35.2 W
- System wattage43.0 W
- Controllability0-10V dimmable
- Color rendering indexRa > 90
- Luminaire lumens5042 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- RAL:
- Bronze (BRZ)
- White (WHT)
- CUS:



Building element · Asymmetric · Twin

	LED	A	B	C
B84241	35.2 W	9 1/2	20 3/8	177 1/8

Type:

BEGA Product:

Project:

Modified:

Available options

- B71140 Direct burial anchorage (replaces included anchorage kit, pre-shippable)
- CUS Custom finish
- FSC Fusing
- MGU Marine grade undercoat
- RAL RAL finish

Included (available for pre-shipment)

- B79802 Buried anchorage kit

