

Application

Twin pole-top luminaire with asymmetric wide beam light distribution (Type II). The wide spread light distribution is ideally suited for illuminating roads and pathways. Slip fits 3" O.D. pole top or tenon.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 66

Weight: 25.1 lbs.

EPA (Effective projection area): 1.0 sq. ft.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage31.6W
- System wattage40.0W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens4782 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- RAL:
- Bronze (BRZ)
- White (WHT)
- CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

- CUSCustom finish
- FSCFusing
- MGUMarine grade undercoat
- RALRAL finish



Pole-top luminaire · Asymmetric wide beam · Twin

	LED	A	B	C
B84254	31.6W	8 ⁷ / ₈	10 ⁵ / ₈	38 ³ / ₄

