## Application

Light building element with asymmetric wide beam light distribution. Light building elements are luminous design features for public areas. They are usually suited for delineating and structuring interior and exterior spaces such as landscape areas, plazas, building entrances and atria.

#### Materials

Clear safety glass with optical texture

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy

Extruded aluminum pole shaft

High temperature silicone gasket Galvanized steel anchorage

Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 65

Weight: 76.7 lbs.

EPA (Effective projection area): 9.7 sq. ft.

#### Flectrica

Operating voltage 120-277VAC
Minimum start temperature -30° C
LED module wattage 30.8 W
System wattage 37.0 W

Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 5040 lm

Luminaire lumens 5040 lm LED service life (L70) 60000 hrs

## LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

#### Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

## Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:



### **Building element** · Asymmetric wide beam · Twin

	LED	Α	В	С
B84275	30.8 W	91/4	18	137³/ <sub>4</sub>

Type:

**BEGA Product:** 

Project: Modified:

# Available options

B71140 Direct burial anchorage (replaces included

anchorage kit, pre-shippable)

CUS Custom finish

FSC Fusing

MGU Marine grade undercoat

RAL RAL finish

### Included (available for pre-shipment)

B79802 Buried anchorage kit

