

Application
A round in-grade intended for the illumination of walls and building facades. Designed to bear pressure loads up to 11,000 lbs. from vehicles with pneumatic tires. The luminaire must not be used for traffic lanes where it is subject to horizontal pressure from vehicles braking, accelerating, or changing direction.

Materials
Clear safety glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection
Corrosion-resistant 304 grade stainless steel
High temperature silicone gasket
Fully potted waterstopper cable
Mechanically captive stainless steel fasteners
Pure anodized aluminum reflector surface

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 68

Weight: 30.9lbs.

Electrical
Operating voltage 120-277V AC
Minimum start temperature -30° C
LED module wattage 46.8 W
System wattage 53.0 W
Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 5052 lm
LED service life (L70) 60000 hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
#4 brushed stainless steel. Custom colors are not available.

Type:
BEGA Product:
Project:
Modified:

Available options
FSC Fusing
NSL Non-skid lens

Included (available for pre-shipment)
BB84290 Installation housing



In-grade luminaire · Wall washer					
	LED	□	A	B	C
B84300	46.8 W	40°x53°	13	14	10

