

Application
With an elegant form and extraordinary glare control, this pole top luminaire provides visual interest both day and night. Designed to illuminate large parking areas, roadways and walkways. Provided with slip fitter to fit 3" O.D. poles.

Materials
Optically textured UV-stabilized acrylic diffuser
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Mechanically captive stainless steel fasteners
Integral surge protector
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 61.7 lbs.

EPA (Effective projection area): 1.6 sq. ft.

Electrical
Operating voltage 120-277V AC
Minimum start temperature -30° C
LED module wattage 100.8 W
System wattage 114.0 W
Controllability 0-10V dimming down to 1%
Color rendering index Ra > 80
Luminaire lumens 8978 lm
LED service life (L70) 60000 hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors
Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:

Type:
BEGA Product:
Project:
Modified:

Available options
CUS Custom finish
FSC Fusing
MGU Marine grade undercoat
RAL RAL finish



Edge-lit pole-top luminaire · Asymmetric			
	LED	A	B
B84306	100.8 W	29 1/2	32 3/8

