Application

A large-scale, high-output floodlight with mounting yoke designed to illuminate bridges, monuments, building facades or large signage. For use in ambient temperatures that do not exceed 25° C.

Materials

Clear safety glass

Marine grade, copper free (\leq 0.3% copper content) A360.0 aluminum alloy

High temperature silicone gasket

Mechanically captive stainless steel fasteners

Stainless steel mounting yoke

Pure anodized aluminum reflector surface

Composite concentric ring louver

BEGA Hybrid Optics®

Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 67

Weight: 23.8 lbs.

EPA (Effective projection area): 1.3 sq. ft.

Electrical

Operating voltage 120-277V AC
Minimum start temperature 40° C
Maximum ambient temperature 25° C
LED module wattage 97.2W
System wattage 122.0W
Controllability 0-10V dimmable

Color rendering index Ra > 80 Luminaire lumens 4117 lm LED service life (L70) 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details


Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
Natural Bronze (NTB) RAL:

CUS:



High-performance floodlight · Very narrow beam

	LED		Α	В	С
B84328	97.2W	4.8°	143/4	16	67/8

Type:

BEGA Product:

Project: Modified:

Available options

B71110 Glare shield · 180° CUS Custom finish

FSC Fusing

MGU Marine grade undercoat NTB Natural bronze (premium finish)

RAL RAL finish

VRY Vibration resisting yoke

Available accessories

B70761 Cross beam · 3 floodlights
B70762 Pole cap · 2 floodlights
B70763 Pole cap · 3 floodlights
B70764 Pole cap · 4 floodlights
B70765 Cross beam · 6 floodlights
B79550 Pole mount arm
B79551 Wall mount arm
B79555 Pole-top mounting hub

See individual accessory spec sheet for details.

