

Application

A large-scale, high-output floodlight with mounting yoke designed to illuminate bridges, monuments, building facades or large signage. For use in ambient temperatures that do not exceed 25° C.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Stainless steel mounting yoke
- Pure anodized aluminum reflector surface
- Composite concentric ring louver
- BEGA Hybrid Optics®
- Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 67

Weight: 41.9lbs.

EPA (Effective projection area): 2.2 sq. ft.

Electrical

- Maximum ambient temperature 25° C
- LED module wattage 250.2W
- System wattage 285.0W
- Color rendering index Ra > 80
- Luminaire lumens 8597 lm
- LED service life (L70) 60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- | | |
|----------------------|--------------|
| Black (BLK) | Bronze (BRZ) |
| Silver (SLV) | White (WHT) |
| Natural Bronze (NTB) | RAL: |
| CUS: | |

Type:

BEGA Product:

Project:

Modified:


Available options

- | | |
|--------|---------------------------------|
| B71101 | Glare shield · 180° |
| CUS | Custom finish |
| FSC | Fusing |
| MGU | Marine grade undercoat |
| NTB | Natural bronze (premium finish) |
| RAL | RAL finish |
| VRY | Vibration resisting yoke |

Available accessories

- | | |
|--------|----------------------------|
| B70761 | Cross beam · 3 floodlights |
| B70762 | Pole cap · 2 floodlights |
| B70763 | Pole cap · 3 floodlights |
| B70764 | Pole cap · 4 floodlights |
| B70765 | Cross beam · 6 floodlights |
| B79550 | Pole mount arm |
| B79551 | Wall mount arm |
| B79555 | Pole-top mounting hub |

See individual accessory spec sheet for details.



High-performance floodlight · Very narrow beam

	LED	□	A	B	C
B84329	250.2W	4.7°	19 ¹ / ₂	20 ³ / ₄	8 ⁵ / ₈

