

Application

Compact performance floodlight with 1/2" I.P.S. nipple for use with a variety of mounting accessories. Designed to spotlight architectural features, landscaping, and signage. Pair with a variety of optical accessories.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- 316 stainless steel 1/2" IPS threaded nipple
- Pure anodized aluminum reflector surface
- Composite concentric ring louver
- BEGA Hybrid Optics®

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 4.9 lbs.

EPA (Effective projection area): 0.22 sq. ft.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage7.0W
- System wattage10.0W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens365lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- Natural Bronze (NTB)
- CUS:
- Bronze (BRZ)
- White (WHT)
- RAL:

Type:

BEGA Product:

Project:

Modified:


Available options

- CUSCustom finish
- FSCFusing
- MGUMarine grade undercoat
- NTBNatural bronze (premium finish)
- RALRAL Classic, matte finish

Available accessories

- B19593Surface mount conduit wiring box
- B19594Direct burial wiring box
- B70204Earth spike
- B70249Pole cap · 3" O.D. pole tenon
- B70252Wood screw
- B70280Tube clamp
- B70283Screw clamp
- B70379Pole mount arm · 1/2" I.P.S. nipple floodlights
- B71042Pole coupler
- B71118Glare shield · 180°
- B79511Mounting block
- B79829Glare shield · 360°

See individual accessory spec sheet for details.



Performance floodlight · Very narrow beam

	LED	β	A	B	C
B84330	7.0W	5°	5 ³ / ₄	8 ³ / ₄	4 ³ / ₄

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805)684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2025 Updated 09/12/25

