

Application

Single pole-top luminaire with asymmetric light distribution ideal for the illumination of roadways, squares, driveways and pedestrian areas while meeting full cut-off requirements. Slip fits 3" O.D tenon.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 66

Weight: 14.1 lbs.

EPA (Effective projection area): 0.7 sq. ft.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage55.3 W
- System wattage61.0 W
- Controllability0-10V dimming down to 1%
- Color rendering indexRa > 80
- Luminaire lumens6672 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish


All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)Bronze (BRZ)
- Silver (SLV)White (WHT)
- RAL:CUS:

Type:
BEGA Product:
Project:
Modified:

- Available options
- CUSCustom finish
 - FSCFusing
 - MGUMarine grade undercoat
 - RALRAL finish



Pole-top luminaire · Asymmetric · Single			
	LED	A	B
B84407	55.3 W	8 ⁷ / ₈	11 ¹ / ₂

