

Application

Compact performance floodlight with mounting canopy for mounting to horizontal or vertical surfaces. Designed to spotlight architectural features, landscaping or signage. Pair with a variety of optical accessories.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Pure anodized aluminum reflector surface
- Composite concentric ring louver
- BEGA Hybrid Optics®

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 6.2 lbs.

EPA (Effective projection area): 0.32 sq. ft.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage12.8 W
- System wattage18.0 W
- Controllability0-10V, TRIAC, and ELV dimmable
- Color rendering indexRa > 80
- Luminaire lumens518 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- | | |
|----------------------|--------------|
| Black (BLK) | Bronze (BRZ) |
| Silver (SLV) | White (WHT) |
| Natural Bronze (NTB) | RAL: |
| CUS: | |

Type:
BEGA Product:
Project:
Modified:


Available options

- | | |
|-----|---------------------------------|
| CUS | Custom finish |
| FSC | Fusing |
| MGU | Marine grade undercoat |
| NTB | Natural bronze (premium finish) |
| RAL | RAL finish |

Available accessories

- | | |
|--------|---------------------|
| B71111 | Glare shield · 180° |
| B79830 | Glare shield · 360° |

See individual accessory spec sheet for details.



Performance floodlights · Very narrow beam

	LED	□	A	B	C	D
B84408	12.8 W	5°	6 ⁷ / ₈	10 ¹ / ₈	5	4

