

Application

An unshielded bollard with safety guard and 180° distribution for illumination of gardens and residential areas. Anchorage unit intended to be cast directly in concrete surfaces.

Materials

Hand-blown three-ply opal glass  
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
High temperature silicone gasket  
Galvanized steel anchorage

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 15.0lbs.

Electrical

|                           |                                |
|---------------------------|--------------------------------|
| Operating voltage         | 120-277VAC                     |
| Minimum start temperature | -30° C                         |
| LED module wattage        | 8.0W                           |
| System wattage            | 10.0W                          |
| Controllability           | 0-10V, TRIAC, and ELV dimmable |
| Color rendering index     | Ra > 80                        |
| Luminaire lumens          | 173lm                          |
| LED service life (L70)    | 60000hrs                       |

LED color temperature

4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

|                      |              |
|----------------------|--------------|
| Black (BLK)          | Bronze (BRZ) |
| Silver (SLV)         | White (WHT)  |
| Natural Bronze (NTB) | RAL:         |
| CUS:                 |              |

Type:

BEGA Product:

Project:

Modified:

Available options

|     |                                 |
|-----|---------------------------------|
| CUS | Custom finish                   |
| FSC | Fusing                          |
| MGU | Marine grade undercoat          |
| NTB | Natural bronze (premium finish) |
| RAL | RAL finish                      |



| Bollard · Hardscape base · 180° |      |       |        |
|---------------------------------|------|-------|--------|
|                                 | LED  | A     | B      |
| B84424                          | 8.0W | 5 1/2 | 35 3/4 |

