

Application
An unshielded bollard with safety guard and 360° distribution for even illumination of gardens and residential areas. Anchorage unit intended to be cast directly in concrete surfaces.

Materials
Hand-blown three-ply opal glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Self-expanding sleeve anchors for pre-cast concrete

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 15.0lbs.

Electrical	
Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	8.0W
System wattage	10.0W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 80
Luminaire lumens	364 lm
LED service life (L70)	60000hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors	
Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:
BEGA Product:
Project:
Modified:

Available options	
CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL finish



Bollard · Hardscape base · 360°		
	LED	A B
B84430	8.0W	5 1/2 35 5/8

