

**Application**

Pole-top luminaire with symmetric light distribution and shallow height. The symmetric light distribution is ideal for illuminating squares, plazas and other open areas.

**Materials**

Clear UV-stabilized acrylic diffuser  
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
 Stainless steel hardware  
 Mounting hardware included  
 Pure anodized aluminum reflector surface

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 65

**Weight:** 14.1 lbs.

**Electrical**

LED module wattage	24.0W
System wattage	28.0W
Color rendering index	Ra > 80
Luminaire lumens	3600 lm
LED service life (L70)	60000 hrs

**LED color temperature**

4000K (K4)  
 3500K (K35)  
 3000K (K3)  
 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**


All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

**Available colors**

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

**Available options**

CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
RAL	RAL Classic, matte finish



**Pole-top luminaire · Symmetric**

	LED	A	B
<b>B84481</b>	24.0W	19 <sup>5</sup> / <sub>8</sub>	8 <sup>7</sup> / <sub>8</sub>

