


BEGA

Photometric Filename: 84508.IES

TEST: BE_84508
TEST LAB: BEGA
DATE: 9/30/2016
LUMINAIRE: 84 508
LAMP: 9.8W LED




Characteristics


NEMA Type	7 H x 6 V
Maximum Candela	608.9
Maximum Candela Angle	-13 H 0 V
Horizontal Beam Angle (50%)	90.2
Vertical Beam Angle (50%)	77.5
Horizontal Field Angle (10%)	131.5
Vertical Field Angle (10%)	107.9
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Beam Lumens	809
Beam Efficiency	N.A.
Field Lumens	1076
Field Efficiency	N.A.
Spill Lumens	38
Luminaire Lumens	1114
Total Efficiency	N.A.
Total Luminaire Watts	12
Ballast Factor	1.00

Zonal Lumen Summary

Zone	Lumens
0-10	56.13
10-20	166.50
20-30	250.13
30-40	266.71
40-50	207.94
50-60	108.81
60-70	40.79
70-80	11.49
80-90	1.60
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00



Mounting Height = 8 ft. Grid Spacing = 5 ft.



In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2018

2/14/2018