## Application

Compact performance floodlight with 1/2" I.P.S. nipple for use with a variety of mounting accessories. Designed to illuminate architectural features, landscaping, signage, and for general illumination of a space. Pair with a variety of optical accessories.

#### Materials

Clear safety glass

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy Silicone applied robotically to casting, plasma treated for increased adhesion

High temperature silicone gasket
Mechanically captive stainless steel fasteners
316 stainless steel 1/2" IPS threaded nipple
Pure anodized aluminum reflector surface
Composite concentric ring louver

**NRTL** listed to North American Standards, suitable for wet locations Protection class IP 65

Weight: 5.3 lbs.

BEGA Hybrid Optics®

EPA (Effective projection area): 0.3 sq. ft.

#### Electrical

Operating voltage 120-277V AC Minimum start temperature -30° C LED module wattage 38.1 W System wattage 43.0 W

Controllability 0-10V dimming down to 1%

Color rendering index Ra > 90 Luminaire lumens 2244 lm LED service life (L70) 60000 hrs

# LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

#### Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

## Available colors

 Black (BLK)
 Bronze (BRZ)

 Silver (SLV)
 White (WHT)

 RAL:
 CUS:



### Performance floodlight · Very narrow beam

	LED	β	Α	В	С
B84526	38.1 W	11°	6 <sup>7</sup> / <sub>8</sub>	10	37/8

Type:

**BEGA Product:** 

Project: Modified:

#### Available options

B71113 Elliptical spread lens (Not compatible with

internal louver)

CUS Custom finish FSC Fusing

MGU Marine grade undercoat

RAL RAL finish

#### Available accessories

B19593	Surface mount conduit wiring box
B19594	Direct burial wiring box
B70249	Pole cap · 3" O.D. pole tenon
B70252	Wood screw
B70280	Tube clamp
B70283	Screw clamp
B70379	Pole mount arm · 1/2" I.P.S. nipple floodlights
B71042	Pole coupler
B71111	Glare shield · 180°
B79511	Mounting block

See individual accessory spec sheet for details.

