## Application

A large-scale, high-output floodlight with mounting yoke designed to illuminate bridges, monuments, building facades or large signage. For use in ambient temperatures that do not exceed 45° C.

#### Materials

Clear safety glass

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy High temperature silicone gasket

Stainless steel mounting yoke Composite concentric ring louver

Pure anodized aluminum reflector surface

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 67 **Weight:** 49.0 lbs.

EPA (Effective projection area): 2.2 sq. ft.

## Electrical

Operating voltage 120-277VAC -30° C Minimum start temperature Maximum ambient temperature 45° C LED module wattage 303.0W System wattage 236.0W Controllability 0-10V dimmable Color rendering index Ra > 80 Luminaire lumens 41081 lm LED service life (L70) 60000 hrs

## LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27) 2200K (K22)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

# Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

## Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:

Type:

**BEGA Product:** 

Project: Modified:

#### Available options

B71101 Glare shield · 180° B79509 Glare shield · 360° CUS Custom finish MGU Marine grade undercoat


RAL RAL finish

### Available accessories

B70761	Cross beam $\cdot$ 3 floodlights
B70762	Pole cap · 2 floodlights
B70763	Pole cap · 3 floodlights
B70764	Pole cap · 4 floodlights
B70765	Cross beam · 6 floodlights
B79550	Pole mount arm
B79551	Wall mount arm
B79555	Pole-top mounting hub

See individual accessory spec sheet for details.





High-performance floodlight · Narrow beam	

	LED	β	Α	В	С
B84541	303.0W	21°	19 <sup>1</sup> / <sub>2</sub>	207/8	121/4