

Application

A large-scale, high-output floodlight with mounting yoke designed to illuminate bridges, monuments, building facades or large signage. For use in ambient temperatures that do not exceed 45° C.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Stainless steel mounting yoke
- Pure anodized aluminum reflector surface

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 67

Weight: 48.5lbs.

EPA (Effective projection area): 2.2 sq. ft.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-30° C
- Maximum ambient temperature45° C
- LED module wattage303.0W
- System wattage332.0W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens41936lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)
- 2200K (K22)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)

Bronze (BRZ)

Silver (SLV)

White (WHT)

Natural Bronze (NTB)

RAL:

CUS:

Type:

BEGA Product:

Project:

Modified:

Available options

- B71101

B71105

B79509

CUS

MGU

NTB

RAL

Glare shield · 180°

Concentric ring louver

Glare shield · 360°

Custom finish

Marine grade undercoat

Natural bronze (premium finish)

RAL finish

Available accessories

- B70761

B70762

B70763

B70764

B70765

B79550

B79551

B79555

Cross beam · 3 floodlights

Pole cap · 2 floodlights

Pole cap · 3 floodlights

Pole cap · 4 floodlights


Cross beam · 6 floodlights

Pole mount arm

Wall mount arm

Pole-top mounting hub

See individual accessory spec sheet for details.



High-performance floodlight · Wide beam					
	LED		A	B	C
B84542	303.0W	48°	19 ¹ / ₂	20 ⁷ / ₈	12 ¹ / ₄

