Application

Compact performance floodlight with 1/2" I.P.S. nipple for use with a variety of mounting accessories. Designed to illuminate architectural features, landscaping, signage, and for general illumination of a space. Pair with a variety of optical accessories.

Materials

Clear safety glass

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy Silicone applied robotically to casting, plasma treated for increased adhesion

High temperature silicone gasket
Mechanically captive stainless steel fasteners
316 stainless steel 1/2" IPS threaded nipple
Pure anodized aluminum reflector surface
BEGA Hybrid Optics®

 $\ensuremath{\mathsf{NRTL}}$ listed to North American Standards, suitable for wet locations Protection class IP 65

Weight: 12.4 lbs.

EPA (Effective projection area): 0.5 sq. ft.

Electrical

Operating voltage 120-277V AC
Minimum start temperature -40° C
LED module wattage 64.5 W
System wattage 72.0 W

Controllability 0-10V dimmable

Color rendering index Ra > 90 Luminaire lumens 4804 lm LED service life (L70) 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
Natural Bronze (NTB) RAL:
CUS:



Performance floodlight · Very narrow beam

	LED		Α	В	С
B84547	64.5 W	11°	97/8	133/4	51/2

Type:

BEGA Product:

Project: Modified:

Available options

B71074 Elliptical spread lens (Not compatible with

internal louver)

CUS Custom finish FSC Fusing

MGU Marine grade undercoat

NTB Natural bronze (premium finish)

RAI RAI finish

Available accessories

B19593	Surface mount conduit wiring box			
B19594	Direct burial wiring box			
B70204	Earth spike			
B70249	Pole cap · 3" O.D. pole tenon			
B70252	Wood screw			
B70280	Tube clamp			
B70283	Screw clamp			
B70379	Pole mount arm · 1/2" I.P.S. nipple floodlights			
B71072	Glare shield · 180°			
B79511	Mounting block			

See individual accessory spec sheet for details.

