

Application

Compact performance floodlights for use with BEGA profile poles. Designed to spotlight architectural features, landscaping or signage. Pair with a variety of optical accessories. The BEGA profile pole system is an easy way to elevate, mount, and direct up to 8 floodlights to meet any directed lighting needs.

Materials

Clear safety glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Stainless steel hardware
Pure anodized aluminum reflector surface
BEGA Hybrid Optics®
Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 4.9 lbs.

EPA (Effective projection area): 0.22 sq. ft.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	7.0W
System wattage	10.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	365lm
LED service life (L70)	60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Silver (SLV)	Black (BLK)
Bronze (BRZ)	White (WHT)
RAL:	CUS:

Type:

BEGA Product:

Project:

Modified:


Available options

CUS	Custom finish
MGU	Marine grade undercoat
RAL	RAL Classic, matte finish

Available accessories

B71118	Glare shield · 180°
B79829	Glare shield · 360°

See individual accessory spec sheet for details.



Profile performance floodlights · Very narrow beam

	LED	β	A	B	C
B84660	7.0W	5°	5 ³ / ₄	8 ³ / ₄	4 ³ / ₄

