

Application

Bollard luminaire with unshielded light distribution that provides brilliant illumination of ground surfaces as well as high levels of vertical illuminance perfect for illuminating people or architectural elements.

Materials

Clear safety glass with white ceramic coating
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Self-expanding sleeve anchors for pre-cast concrete
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 26.7 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	12.3 W
System wattage	14.5 W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	907 lm
LED service life (L70)	60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:


BEGA Product:

Project:

Modified:

Available options

CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL Classic, matte finish



Bollard · Unshielded				
	LED	A	B	C
B84670	12.3 W	13 ³ / ₈	31 ¹ / ₂	4

