

Application

Bollard luminaires with wide spread light distribution that is perfect for the illumination of walkways and paths.

Materials

Clear safety glass with optical texture
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Silicone applied robotically to casting, plasma treated for increased adhesion
Self-expanding sleeve anchors for pre-cast concrete
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 18.0lbs.

Electrical

Operating voltage120-277VAC
Minimum start temperature-30° C
LED module wattage12.3W
System wattage14.5W
Controllability0-10V dimmable
Color rendering indexRa > 80
Luminaire lumens1023lm
LED service life (L70)60000hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)Bronze (BRZ)
Silver (SLV)White (WHT)
Natural Bronze (NTB)RAL:
CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

CUSCustom finish
FSCFusing
MGUMarine grade undercoat
NTBNatural bronze (premium finish)
RALRAL finish



Bollard · Directed light · wide spread				
	LED	A	B	C
B84673	12.3W	13 ³ / ₈	15 ³ / ₄	4

