

Application

The BEGA profile pole system is an easy way to elevate, mount, and aim up to eight BEGA floodlights to meet any directed lighting needs. Two performance floodlights fit into each profile groove on the pole. Up to eight floodlights with different outputs and distributions can therefore be arranged for the desired illumination. Suitable for installation in wind zones with a maximum wind speed up to 100 MPH per EN 60598.

Materials

- Aluminum structure
- Extruded aluminum pole shaft
- Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
- Covered handhole with hardware and grounding provisions provided
- High temperature silicone gasket
- Stainless steel hardware
- Anchor bolts conform to ASTM F1554 Grade 55 with L bend on one end and galvanized minimum 12" on threaded end
- Anchor bolts provided with (2) hex nuts and (2) flat washers
- Anchorage must be buried

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 64.4 lbs.

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- | | |
|--------------|--------------|
| Black (BLK) | Bronze (BRZ) |
| Silver (SLV) | White (WHT) |
| RAL: | CUS: |

Type:

BEGA Product:

Project:

Modified:

Available options

- | | |
|--------|--|
| B71207 | Direct burial anchorage (replaces included anchorage kit, pre-shippable) |
| CUS | Custom finish |
| MGU | Marine grade undercoat |
| RAL | RAL finish |

Included (available for pre-shipment)

- | | |
|--------|---------------|
| B79827 | Anchorage kit |
|--------|---------------|



Square aluminum · Square straight

	A	B	C
B84700	4 ³ / ₄	157 ³ / ₄	24 ³ / ₄

