

System building element pole · Direct burial · 2 adjustable floodlights

BEGA

Application

Building elements are luminous design features for public spaces. They are ideally suited for delineating and structuring spaces such as plazas, building entrances, and atria. An integral floodlight may be used to illuminate architectural details, landscaping, or signage. The floodlight has an adjustable inclination angle of 30° and can be rotated 360°. An accompanying building element head must be selected for proper installation. Suitable for installation in wind zones with a maximum wind speed up to 115 MPH per EN 60598.

Materials

Clear safety glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Extruded aluminum pole shaft
Covered handhole with hardware and grounding provisions provided
Stainless steel hardware
Anchorage must be buried
BEGA Hybrid Optics®
Pure anodized aluminum reflector surface
Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 76.1 lbs.

Electrical

Operating voltage 120-277VAC
Minimum start temperature -30° C
LED module wattage 24.0W
System wattage 28.0W
Controllability 0-10V, TRIAC, and ELV dimmable
Color rendering index Ra > 90
Luminaire lumens 1412lm
LED service life (L70) 60000hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:



Type:

BEGA Product:

Project:

Modified:

Available options

B10014 Elliptical spread lens
B71215 Concentric ring louver
CUS Custom finish
MGU Marine grade undercoat
RAL RAL Classic, matte finish



System building element pole · Direct burial · 2 adjustable floodlights

	LED	β	A	B	C
B84716	24.0W	22°	6 ³ / ₄	153 ³ / ₈	31 ¹ / ₂

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805)684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2025 Updated 09/12/25

System building elements summary

BEGA

This overview provides a compact summary of the possibilities for combining the various building element heads with poles and their additional functions.

For each building element head you can find matching poles with and without components.

System building elements with compatible poles		 Symmetric			 Asymmetric			 Unshielded			 Unshielded			 Symmetric			 Asymmetric		
Ø in inches		ø5 ¼	ø6 ¾	ø8 ⅝	ø5 ¼	ø6 ¾	ø8 ⅝	ø5 ¼	ø6 ¾	ø8 ⅝	ø5 ¼	ø5 ¼	ø5 ¼	ø5 ¼	ø5 ¼	ø5 ¼			
	Base plate • without components	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
	Direct burial • without components	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
	Base plate • wood	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
	Direct burial • wood	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•			
	Base plate • 1 adjustable floodlight		•	•		•	•		•	•									
	Direct burial • 1 adjustable floodlight		•	•		•	•		•	•									
	Base plate • 2 adjustable floodlights		•	•		•	•		•	•									
	Direct burial • 2 adjustable floodlights		•	•		•	•		•	•									

Compatible heads · Ø6 3/4

System building element head · Symmetric			
	LED	A	B
B84816	29.4 W	6 3/4	23 3/4
System building element head · Asymmetric			
	LED	A	B
B84819	29.4 W	6 3/4	23 3/4
System building element head · Unshielded			
	LED	A	B
B84733	45.6 W	6 3/4	52 1/4