

Application

Building elements are luminous design features for public spaces. They are ideally suited for delineating and structuring spaces such as plazas, building entrances, and atria. Simply order the building element head plus a required building element pole in wood or metal with optional integral components. Both modules can be joined together easily and quickly during installation.

Materials

White UV-stabilized acrylic diffuser
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Stainless steel hardware
Integral surge protector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 20.5 lbs.

Electrical

Operating voltage 120-277V AC
Minimum start temperature -30° C
LED module wattage 23.2 W
System wattage 30.0 W
Controllability 0-10V dimming down to 1%
Color rendering index Ra > 80
Luminaire lumens 2704 lm
LED service life (L70) 60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish


All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:

Type:
BEGA Product:
Project:
Modified:

Available options
CUS Custom finish
DALI-2 Digital addressable lighting interface
FSC Fusing
MGU Marine grade undercoat
RAL RAL Classic, matte finish



System building element head · Unshielded				
	LED	A	B	C
B84737	23.2 W	20 ¹ / ₈	21 ⁵ / ₈	5 ¹ / ₄










System building elements summary

BEGA

This overview provides a compact summary of the possibilities for combining the various building element heads with poles and their additional functions.

For each building element head you can find matching poles with and without components.

System building elements with compatible poles		 Symmetric			 Asymmetric			 Unshielded			 Unshielded			 Symmetric			 Asymmetric		
Ø in inches		ø5 1/4	ø6 3/4	ø8 3/8	ø5 1/4	ø6 3/4	ø8 3/8	ø5 1/4	ø6 3/4	ø8 3/8	ø5 1/4			ø5 1/4			ø5 1/4		
	Base plate • without components	•	•	•	•	•	•	•	•	•	•			•			•		
	Direct burial • without components	•	•	•	•	•	•	•	•	•	•			•			•		
	Base plate • wood	•	•	•	•	•	•	•	•	•	•			•			•		
	Direct burial • wood	•	•	•	•	•	•	•	•	•	•			•			•		
	Base plate • 1 adjustable floodlight		•	•		•	•			•	•								
	Direct burial • 1 adjustable floodlight		•	•		•	•			•	•								
	Base plate • 2 adjustable floodlights		•	•		•	•			•	•								
	Direct burial • 2 adjustable floodlights		•	•		•	•			•	•								

Compatible poles · Ø5 1/4

System building element pole · Base plate			
	A	B	C
B84709	5 1/4	138 1/4	13 3/8

System building element pole · Direct burial			
	A	B	C
B84708	5 1/4	138 1/8	31 1/2

Wood system building element pole · Base plate			
	A	B	C
B84711	5 1/4	138 1/2	13 3/8

Wood system building element pole · Direct burial			
	A	B	C
B84710	5 1/4	138 5/8	31 1/2